



Qrystal P8

Mono-Crystalline

550~570W

0~+5W POWER TOLERANCE

- High efficiency PERC single glass solar module
- Stronger properties, PID resistance, reduced hot spot loss
- Better temperature coefficient
- Harsh environmental adaptation

12 years material process warranty

12

25 years power linear warranty

25

A sound quality management
system and product certification

IEC61215(2016), IEC61730(2016)

ISO9001:2015: Quality management system



ISO14001:2015: Environmental management system

ISO45001:2018: Occupational health and safety management system



21.1%
MAXIMUM CONVERSION0~+5W
POWER TOLERANCE0.55%
0.55% PER YEAR OVER 25 YEARSHalf-Cut Module
LOWER TEMPERATURE COEFFICIENT

Mechanical Diagrams


Length: $\pm 2\text{mm}$ Width: $\pm 2\text{mm}$ Thickness: $\pm 1\text{mm}$ Hole pitch: $\pm 2\text{mm}$ 

Packing Standard

Container Capacity(40HQ)

37pcs/pallet, 20pallets/ctns, 740pcs/ctn

Curve Figure



Specification

Cell Type	Mono Crystalline
No. of Cells	144 [2x(6x12)] pcs
Dimension	2382x1134x30mm
Weight	28.4kg $\pm 3\%$
Glass	3.2mm
Frame	Anodized Aluminum Alloy
Junction Box	IP68
Cable Length	300mm,1200mm (can be customized)

Electrical Parameters

Module Type	QN-550HT-1		QN-555HT-1		QN-560HT-1		QN-565HT-1		QN-570HT-1	
	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power (Pmax)	555	419	555	419	560	423	565	427	570	433
Maximum Power Voltage (Vmp)	41.39	38.43	41.39	38.43	41.70	38.72	42.01	39.00	42.31	39.28
Maximum Power Current (Imp)	13.41	10.91	13.41	10.91	13.43	10.92	13.45	10.93	13.47	10.95
Open Circuit Voltage (Voc)	49.03	45.45	49.03	45.45	49.42	45.80	49.91	46.24	50.15	46.47
Short Circuit Current (Isc)	14.15	11.54	14.15	11.54	14.17	11.56	14.19	11.61	14.21	11.63
Module Efficiency - η_m (%)	20.3		20.5		20.7		20.9		21.1	

Load Capacity

Max Load Front	5400Pa
Max Load Back	2400Pa
Through Hail Testing	25mm Diameter, Impact Speed 23m/s

Temperature Coefficient (STC Test)

Temperature Coefficient of Isc	+0.04%/°C
Temperature Coefficient of Voc	-0.25%/°C
Temperature Coefficient of Pmax	-0.34%/°C

Operation Parameters

Operational Temperature	-40°C~+85°C
Maximum System Voltage	1500VDC (IEC)
Maximum Series Fuse Rating	30A
Power Tolerance	0~+5W
Nominal Operating Cell Temperature (NOCT)	45 ± 2 °C
Safety Class	class II

STC: Irradiance:1000W/m² | Battery temperature: 25°C | Atmospheric=1.5NOCT: Irradiance:800W/m² | Ambien temperature: 20°C | Atmospheric=1.5 | Wind speed 1m/sD5 Greenland Window Building
Nonghua Road
Yuhuatai District, Nanjing, China
www.q-sunsolar.com / www.qclenergy.com